



Section 1. Amendment to the Claims

1. (Currently Amended): A device ~~for attaching~~ attachable to a forklift truck, and thereby aiding in the movement and transport of rolled goods, said device comprising:
 - a pair of parallel rectangular tubes, suitably disposed for the reception of the forks of a forklift truck;
 - wherein said parallel rectangular tubes each have a first end and second end with the first end being compatible for reception of said forks;
 - a vertical support plate, arising above and between said tubes, and substantially perpendicular to said tubes;
 - a pole, extending outward from one face of said vertical support plate, said vertical support plate connecting said tubes to said pole; ~~and~~
 - wherein said vertical support plate with attached pole is positioned at an intermediate point between said first and second end on said parallel rectangular tubes; and
 - ~~a base plate~~ front stabilizer plate ~~attaching~~ attached to said tubes, ~~stably thereby~~ connecting each tube to the other.
2. (Original): The device of claim 1, further comprising side gussets to support said pole and said vertical support plate.
3. (Original): The device of claim 1, further comprising a plurality of locking devices to ensure that the forks of a forklift truck do not disengage from said tubes during operations.
4. (Original): The device of claim 1, further comprising a support collar for securing said pole stably to said vertical support plate.
5. (Original): The device of claim 1, further comprising a means for replaceably removing said pole.
6. (Cancel): ~~The device of claim 4, wherein the means for securing said pole comprises a latching pin securing said pole to said support collar.~~



7. (Original): The device of claim 1, wherein ~~the fork receiving~~ said parallel rectangular tubes are each at least 28 inches long.
8. (Original): The device of claim 1, wherein the fork receiving tubes are substantially parallel, and substantially flush with the leading edge of the device with pole removed.
9. (Original): The device of claim 1, wherein the vertical support plate is at least 13 inches in height.
10. (Original): The device of claim 1, wherein the length of the pole is sufficient for a standard commercial roll of rolled goods to be inserted thereupon, with no length of rolled goods left hanging over the free end of the pole.
11. (Currently Amended): The device of claim 1, wherein the ~~fork receivers~~ pair of rectangular tubes extend entirely outward from the vertical support plate, on the same side thereon as the pole.
12. (Original): The use of the device of claim 1 in connection with the forklift truck to engage and move rolled goods.